

© EPDOC / EPO

PN - JP2000344011 A 20001212
 PD - 2000-12-12
 PR - JP19990154759 19990602
 OPD - 1999-06-02
 TI - DOOR TRIM FOR AUTOMOBILE
 AB - PROBLEM TO BE SOLVED: To prevent exposure of housing articles by closing the opening in a normal time, and to facilitate the use by lighting the inside of a pocket by opening a pocket lid body when using. SOLUTION: In this door trim pocket, the front surface of a recess 2 for pocket formed to a door trim main body 1 is made open and to close freely by a pocket lid body 3 with lower end pivoted to the lower end of the door trim main body, and with upper end inclined a specific angle to the front side. In this case, a lamp 5 to light the inside of the pocket when the pocket lid part 3 is opened is installed to the rear face of the pocket lid body 3.
 IN - GOTO YASUHIRO; URATSU MASAMI; KAWAUCHI HIROSHI
 PA - TAKASHIMAYA NIPPATSU KOGYO
 IC - B60Q3/02; B60J5/04; B60R7/04; B60R13/02; F21Y103/00

© WPI / DERWENT

TI - Door trim for motor vehicle, has pocket cover which is pivotably mounted to door trim main section, and lamp installed to inner side of cover
 PR - JP19990154759 19990602
 PN - JP2000344011 A 20001212 DW200112 B60Q3/02 004pp
 PA - (TAKA-N) TAKASHIMAYA HIHATSU KOGYO KK
 IC - B60J5/04 ;B60Q3/02 ;B60R7/04 ;B60R13/02 ;F21Y103/00
 AB - JP2000344011 NOVELTY - A pocket cover (3) which is openable to a predetermined angle to form a pocket opening (4), has lower end pivotably mounted in a door trim main section (1). The cover is mounted in front surface of recess (2) for pockets formed in main section. A lamp (5) which illuminates when the pocket cover is opened, is provided in inner side of pocket cover.
 - USE - For motor vehicles.
 - ADVANTAGE - Enables clear visibility of goods stored in pocket, even during night, since lamp installed to inner side of cover illuminates when cover is opened.
 - DESCRIPTION OF DRAWING(S) - The figure shows perspective view of pocket in door trim.
 - Door trim main section 1
 - Recess 2
 - Pocket cover 3
 - Opening 4
 - Lamp 5
 - (Dwg. 1/4)
 OPD - 1999-06-02
 AN - 2001-108927 [12]

© PAJ / JPO

PN - JP2000344011 A 20001212
 PD - 2000-12-12
 AP - JP19990154759 19990602
 IN - GOTO YASUHIRO; URATSU MASAMI; KAWAUCHI HIROSHI
 PA - TAKASHIMAYA NIPPATSU KOGYO CO LTD
 TI - DOOR TRIM FOR AUTOMOBILE
 AB - PROBLEM TO BE SOLVED: To prevent exposure of housing articles by closing the opening in a normal time, and to facilitate the use by lighting the inside of a pocket by opening a pocket lid body when using.

- SOLUTION: In this door trim pocket, the front surface of a recess 2 for pocket formed to a door trim main body 1 is made open and to close freely by a pocket lid body 3 with lower end pivoted to the lower end of the door trim main body, and with upper end inclined a specific angle to the front side. In this case, a lamp 5 to light the inside of the pocket when the pocket lid part 3 is opened is installed to the rear face of the pocket lid body 3.

SI - F21Y103/00

I - B60Q3/02 ;B60J5/04 ;B60R7/04 ;B60R13/02